

		Model	CROWN CDCI-09SUD38	CROWN CDCI-12SUD38	FINLUX FDCI-12SS40	FINLUX FDCI-18SS40	FINLUX FDCI-24SS40
Rated Capacity	Cooling	W	2600	3500	3600	5300	7000
	Heating	W	2700	3650	3750	5510	7100
	Dehumidifyin	Kg/h	1.0	1.3	1.5	1.8	2.2
Rated Power Consumption	Cooling	W	778	1080	1150	1625	2000
	Heating	W	715	984	1050	1450	1950
Rated Running Current	Cooling	A	3.4	5.0	5.3	7.1	11.0
	Heating	A	3.2	4.6	5.5	6.3	10.8
Max. Input Power		W	1500	1500	1650	2400	3400
Max. Input Current		A	7.0	7.0	7.5	10.5	15.0
SEER Cooling		W/W	5.7(A+)	5.7(A+)	6.5(A++)	6.13(A++)	6.1(A++)
SCOP Heating		W/W	3.84(A)	3.81(A)	4.15(A+)	4.05(A+)	4.01(A+)
Power supply source		V/Ph/Hz	220~240/1/50	220~240/1/50	220~240/1/50	220~240/1/50	220~240/1/50
Refrigerant			R410a	R410a	R410a	R410a	R410a
Refrigerant Charged		g	800	840	1100	1450	1750
Max. Discharge Pressure		Mpa	4.15	4.15	4.15	4.15	4.15
Max. Suction Pressure		Mpa	1.15	1.15	1.15	1.15	1.15
Air Flow Volume		m ³ /h	500	560	630	770	950
Indoor Unit Sound Pressure		Db(A)	42	42	45	47	52
Outdoor Unit Sound Pressure		Db(A)	52	53	54	57	63
Indoor unit weight(net)		Kg	7	7	10.5	13	18
Outdoor unit weight(net)		Kg	26	27	31	41	54
Compressor Brand			GMCC	GMCC	GMCC	SANYO	SANYO
COMpressor Name			ASN98D32UFZ	ASN108D32UFZ	DA89X1C-20FZ3	C-6RVN93HON	C-6RZ146H1A
Indoor's net dimension		mm	802×265×190	802×265×190	880×286×203	1095×312×207	1095×312×207
Outdoor's net dimension		mm	720×540×260	760×540×260	760×540×260	800×590×300	800×690×300
annual consumption			150	207	212	292	398
			856	950	980	1718	2486