

Model No.			LS 9K BTU	LS 12K BTU	LS 18K BTU	LS 24K BTU	LV 12K BTU	LV 18K BTU	
Nameplate Parameter	Rated Capacity	Cooling	2550(1000-3300)	3550(1200-3800)	5250(1900-5500)	7000(2900-7300)	3550(1200-3800)	5250(1900-5500)	
		Heating	2650(1100-3300)	3550(1000-3800)	5400(1400-5600)	7300(2100-8000)	3550(1000-3800)	5400(1400-5600)	
		Dehumidifying	0,95	1,3	1,86	2,55	1,3	1,86	
	Rated Power Consumption	Cooling	W	789	1099	1580	2180	1099	1580
		Heating	W	732	1002	1500	2020	1002	1500
	Rated Running Current	Cooling	A	3,5	4,97	7,2	10,2	4,97	7,2
		Heating	A	3,3	4,43	6,5	8,8	4,43	6,5
	Max. Input Power	W	1800	1800	3200	3600	1800	3200	
	Max. Input Current	A	8	8	14	16	8	14	
	SEER Cooling	W/W	SEER6.1	SEER6.1	SEER 6.1	SEER 6.1	SEER6.1	SEER 6.1	
	SCOP Heating	W/W	SCOP4.0	SCOP4.0	SCOP 4.0	SCOP 4.0	SCOP4.0	SCOP 4.0	
	Power supply source	V/Ph/Hz	220 ~ 240V-1-50Hz	220 ~ 240V-1-50Hz	220 ~ 240V-1-50Hz	220 ~ 240V-1-50Hz	220 ~ 240V-1-50Hz	220 ~ 240V-1-50Hz	
	Refrigerant		R410A	R410A	R410A	R410A	R410A	R410A	
	Refrigerant Charged	g	800	810	1720	1900	810	1720	
	Max. Discharge Pressure	Mpa	4,15	4,15	4,15	4,15	4,15	4,15	
	Max. Suction Pressure	Mpa	1,15	1,15	1,15	1,15	1,15	1,15	
	Air Flow Volume	m3/h	600	600	1000	1200	600	1000	
	Indoor unit Noise Power	dB (A)	53	53	60	60	53	60	
	Outdoor unit Noise Power	dB (A)	59	60	65	68	60	65	
	Indoor unit Noise Pressure	dB (A)	29/32/34/38	30/33/36/39	33/38/41/45	38/41/44/47	30/33/36/39	33/38/41/45	
Outdoor unit Noise Pressure	dB (A)	52	51	54	55	51	54		
Indoor unit weight (Net)	Kg	10	10	14	16	10	14		
Outdoor unit weight (Net)		26	27	38	50	27	38		
Indoor unit weight (Gross)	Kg	12	12,5	16,5	19	12,5	16,5		
Indoor unit weight (Gross)	Kg	30	31	42	55	31	42		
Indoor unit	Dimension	Net Dimension	mm	800*300*198	800*300*198	970*315*235	1100*330*235	800*300*198	970*315*235
		Packing Dimension	mm	870*370*285	870*370*285	1045*385*320	1180*400*320	870*370*285	1045*385*320
Outdoor unit	Compressor Brand		GMCC	GMCC	Highly	Highly	GMCC	Highly	
	Dimension	Net Dimension	mm	720*540*260	760*540*260	802*535*298	800*690*300	760*540*260	802*535*298
		Packing Dimension	mm	850*615*365	880*600*370	920*615*395	940*750*420	880*600*370	920*615*395
Container Loading 40HC		Units	255	250	195	165	250	195	