

Supplier TOSHIBA CARRIER CORPORATION

Indoor unit RAS-B16J2KVG-E

Outdoor unit RAS-16J2AVG-E

Sound power level

indoor unit (cooling)	dB	58
outdoor unit (cooling)	dB	64
indoor unit (heating)	dB	58
outdoor unit (heating)	dB	66

Refrigerant

Type		R32
Global Warming Potential	kgCO ₂ eq	675

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

Cooling

Energy efficiency class		A++
Design load (P _{designc})	kW	4.2
Seasonal efficiency (SEER)		6.10
Seasonal electricity consumption (Q _{CE}) (*)	kWh/annum	241

(*) Based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located

Heating

		Heating/Average	Heating/Warmer	Heating/Colder
Energy efficiency class		A+	A++	x
Design load (P _{designh})	kW	3.6	1.9	x, x
Seasonal efficiency (SCOP)		4.00	4.90	x, x x
Seasonal electricity consumption (Q _{HE}) (*)	kWh/annum	1259	549	x
Back up heating capacity	kW	0.56		

Declared capacity for heating, at indoor temperature 20°C and outdoor temperature T_j.

T _j = -7°C (P _d h)	kW	3.18	-	x, x x
T _j = 2°C (P _d h)	kW	1.94	1.94	x, x x
T _j = 7°C (P _d h)	kW	1.25	1.25	x, x x
T _j = 12°C (P _d h)	kW	1.03	1.03	x, x x
T _j =bivalent temperature (P _d h)	kW	3.18	1.94	x, x x
T _j =operation limit (P _d h)	kW	2.80	2.80	x, x x
T _j = -15°C (P _d h)	kW	-	-	x, x x

(*) Based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located