Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Hama

Supplier's address: Produktmanagement, Dresdner Strasse 9, 86653 Monheim, DE

Model identifier: 00176597

Type of light source:

High luminance light source:	No		
Colour-tuneable light source:	Yes	Envelope:	-
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Light source cap-type (or other electric interface)	E27		
Lighting technology used:	LED	Non-directional or directional:	NDLS

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consum mode (kWh/10 up to the neares	00 h), rounded	10	Energy efficiency class	G		
dicating if it refe a sphere (360°)	s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	806 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	27006500		
On-mode pow pressed in W	ver (P _{on}), ex-	10,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,43		
(P_{net}) for CLS, e	andby power expressed in W the second dec-	0,43	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen-	Height	120	Spectral power dis-	See image		
sions without separate con- trol gear, light- ing control	Width Depth	60 60	tribution in the range 250 nm to 800 nm, at full-load	in last page		

parts and non- lighting con- trol parts, if any (millime- tre)							
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	60				
		Chromaticity coordi- nates (x and y)	0,460 0,410				
Parameters for LED and OLED lig	t sources:						
R9 colour rendering index value	2	Survival factor	0,90				
the lumen maintenance factor	0,96						
Parameters for LED and OLED mains light sources:							
displacement factor (cos φ1)	0,93	Colour consistency in McAdam ellipses	3				
Claims that an LED light source replaces a fluorescent light source without integrated bal- last of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-				
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,1				

(a)_{'-'} : not applicable;

(b)'_-' : not applicable;

